



polilux

The logo features the word "polilux" in a bold, dark blue, lowercase sans-serif font. A small red dot is positioned above the second 'i'.

Product

Catalogue

I M L W A L



polilux

ABOUT US

Polilux is the youngest and the most dynamic BOPP Manufacturing company in Turkey with its highly experienced team. Polilux is continuously enriching its services and providing business partners excellent material quality. Polilux has a production capacity of 30000 MT of BOPP and 8000 MT of Metallized Products.

By relying on our expert employees and utilizing modern technologies, Polilux delivers solution oriented services and high quality films used in flexible packaging, labeling and other applications with different thicknesses.



QUALITY MANAGEMENT

Polilux provides safe and legal products, services and after sales services with maximum care to satisfy and fulfill requirements and expectations of its business partners.

Polilux is certified with:

- ISO 9001:2015
- BRC/IOP

In compliance with global packaging materials standards Polilux takes required actions always considering product safety and provides legal, high quality products that will not cause any harm to its consumers.

Additionally, Polilux continuously improves its products and efficiency of Quality and Food Safety considering market expectations and its beyond.



ISO 9001:2015



IML

PRODUCT

LPF-432

Density (gr/cm³)

0,55

TYPE

Orange Peel

Thickness *(μ)

55-60-65-70

Very High Yield BOPP Film for IML Applications.
Orange Peel Effect after Injection.

PRODUCT

LPV-432

Density (gr/cm³)

0,62

TYPE

Orange Peel

Thickness *(μ)

60-65

High Yield BOPP Film for IML Applications.
Satin Finish After Injection.

PRODUCT

LPS-332

Density (gr/cm³)

0,89

TYPE

Solid White

Thickness *(μ)

60-70

Solid White BOPP Film for IML Applications.
Glossy Effect after Injection.

* Regular Thickness information is mentioned. Other thicknesses are available upon request.

PRODUCT

LPI-332

Density (gr/cm³)

0,96

TYPE

Solid White

Thickness *(μ)

50-57

Solid White BOPP Film for IML Applications.
Extra Glossy Effect after Injection.

PRODUCT

LPB-132

Density (gr/cm³)

0,91

TYPE

Transparent

Thickness *(μ)

50-57

Transparent BOPP Film for IML Applications.

PRODUCT

LPO-532

Density (gr/cm³)

0,88

TYPE

Transparent

Thickness *(μ)

57

One Side Matt, One Side Clear Gloss BOPP
Film for IML Applications.

WAL

PRODUCT

LRT-431

Density (gr/cm³)

0,71

TYPE

Pearlized

Thickness *(μ)

38

High Yield White Voided BOPP film specially designed for WAL Applications.

PRODUCT

LRT-131

Density (gr/cm³)

0,91

TYPE

Transparent

Thickness *(μ)

35-40

Transparent BOPP Film for WAL Applications.

* Regular Thickness information is mentioned. Other thicknesses are available upon request.

The logo for Polilux, featuring the word "polilux" in a bold, dark blue, lowercase sans-serif font. A small red dot is positioned above the letter "i".

polilux

Polilux Plastik Film Sanayi ve Ticaret A. Ő.
Ulař OSB Mahallesi 105. Sokak No:3/1 59930 Ergene, Tekirdađ, TÜRKiYE
+90 282 686 70 00 info@polilux.com www.polilux.com